



## **10 GAUGE "H" SERIES SINGLE DOOR UNDERBODY BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/20/2020

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 10 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Door is horizontally hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Door is attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door is held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop door down to 180°.
- A three point, stainless steel "T" handle is recessed into the door of the box.
- Top panel of the box forms a drip rail over the door.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **12 GAUGE "H" SERIES SINGLE DOOR UNDERBODY BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/30/2020

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 12 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Door is horizontally hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Door is attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door is held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop door down to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the door of the box.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **14 GAUGE "V" SERIES SINGLE DOOR BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/30/2020

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Door is vertically hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is left hand hinged as standard.
- Welds are full arc welds, no spot welds.
- Door is attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door has a heavy-duty machine chain stops
- Chain is easily detachable to allow door to swing around to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the door of the box.
- Two keys are furnished per box.
- Door can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **14 GAUGE "H" SERIES SINGLE DOOR UNDERBODY BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/30/2020

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Doors are horizontally hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Door is attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door is held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop door down to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the door.
- Two keys are furnished per box.
- Doors can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **14 GAUGE "H-2" SERIES TWO DOOR UNDERBODY BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/30/2020

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Doors are horizontally hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Doors are attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors are held in the open position with heavy-duty machine chain.
- Chains are easily detachable to drop door down to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into each door.
- Two keys are furnished per box.
- Doors can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **14 GAUGE "V-2" SERIES TWO DOOR BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/30/2020

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Doors are vertically hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Both doors to be left hand hinged as standard.
- Welds are full arc welds, no spot welds.
- Doors are attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy-duty machine chain stops.
- Chains are easily detachable to allow doors to swing around to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into each door.
- Two keys are furnished per box.
- Doors can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Doors have a formed knife edge on all 4 sides that contacts the seal when the doors are closed.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **14 GAUGE "V-20" SERIES DOUBLE OVERLAPPING DOOR BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/30/30

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Doors are vertically hinged and constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Leading door to be left hand hinged as standard.
- Welds are full arc welds, no spot welds.
- Doors are attached to the hull of the box with stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy-duty machine chain stops.
- Chains are easily detachable to allow doors to swing around to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the leading door.
- Trailing door has a two point latch with inside release.
- Two keys are furnished per box.
- Leading door can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Doors have a formed knife edge on all 4 sides that contacts the seal when the door are closed.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43S SINGLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 75 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-11/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 42 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at top, 8" wide at the bottom and an overall depth of 13-11/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 44 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-11/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 44 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SB SINGLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **To include the following features:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 75 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLP SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 75 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPA SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 44 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPAB SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-11/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 46 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPAW SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 13-3/16" wide at top, 8" wide at the bottom and an overall depth of 13-11/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage zinc phosphate wash and are finished with a white super durable polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 46 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPB SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 75 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPW SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 99 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPWA SINGLE LID ALUMINUM LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 48 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPWAB SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 50 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPWA SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

44" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 50 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SLPWB SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 99 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SW SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 93 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **43SWB SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

43-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 93 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLP SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPA SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-11/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 49 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPAB SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2015

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 51 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPAW SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 51 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPB SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

48-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPW SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

48-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 109 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPWA SINGLE LID ALUMINUM LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 54 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPWAB SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 56 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPWA SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

49" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 56 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **48SLPWB SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

48-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 109 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50S SINGLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50SA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

51" overall length, 13-11/16" wide at the top, 8" wide at bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage zinc phosphate wash and are finished with a black super durable polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50SAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

51" overall length, 13-11/16" wide at the top, 8" wide at bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50SAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

51" overall length, 13-11/16" wide at the top, 8" wide at bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50SB SINGLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50STS SINGLE LID "SLANT TOP" SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 86 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50STSB SINGLE LID "SLANT TOP" SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 86 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50SW SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 102 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **50SWB SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

50-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 102 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61S SINGLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and has an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 99 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 53 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 55 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 55 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SB SINGLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 99 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLP SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 98 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPA SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 58 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPAB SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 60 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPAW SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 60 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPB SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 98 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPW SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 129 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPWA SINGLE LID ALUMINUM LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 65 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPWAB SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 67 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPWA SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 67 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SLPWB SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 129 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61STS SINGLE LID "SLANT TOP" SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 102 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61STSB SINGLE LID "SLANT TOP" SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 102 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SWA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 64 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SWAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 66 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **61SWAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 66 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLP SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

65-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 102 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPA SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 64 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPAB SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 66 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPAW SINGLE LID ALUMINUM LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 66 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPB SINGLE LID LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- .
- Weight: 102 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPW SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

65-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 134 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPWA SINGLE LID ALUMINUM LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 70 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPWAB SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 72 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPWA SINGLE LID ALUMINUM WIDE LOW PROFILE SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

66" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Small parts storage in the front of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 72 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **65SLPWB SINGLE LID LOW PROFILE WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

65-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
8-3/4" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 134 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67S SINGLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 107 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 57 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion
- Weight: 59 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 13-11/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion
- Weight: 59 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SB SINGLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 107 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67STS SINGLE LID "SLANT TOP" SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 108 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67STSB SINGLE LID "SLANT TOP" SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-1/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray 19-1/2" x 8-7/8" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latch is recessed into the lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 108 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SW SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage zinc phosphate wash, anti-corrosion protection, and finished with a white super durable polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 133 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SWA SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 71 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SWAB SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 73 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SWAW SINGLE LID ALUMINUM SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

68" overall length, 18-11/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".  
6-1/8" mount height.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and welded in with full arc welds.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Full length small parts storage tray is in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 73 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **67SWB SINGLE LID WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

67-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 133 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **88S DOUBLE LID SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

88-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lids are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Two full size stainless steel paddle latches are recessed into the hull of the box, one latch for each lid.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of each lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 139 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **88SB DOUBLE LID SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

88-3/4" overall length, 13-3/16" wide at the top, 8" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lids are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 139 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **88SW DOUBLE LID WIDE SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

88-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lids are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Two full size stainless steel paddle latches are recessed into the hull of the box, one latch for each lid.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of each lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 173 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **88SWB DOUBLE LID WIDE SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

88-3/4" overall length, 18-3/16" wide at the top, 13" wide at the bottom and an overall depth of 13-3/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lids are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Full length small parts storage in the front of the box.
- Full size stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of each lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 173 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ALUMINUM "H" SERIES SINGLE DOOR UNDERBODY BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE AND BLACK DIAMOND TREADPLATE**

Revised 3/30/2020

### **BRIGHT DIAMOND TREADPLATE AND BLACK DIAMOND TREADPLATE.**

#### **TO INCLUDE THE FOLLOWING FEATURES:**

- .100 bright diamond treadplate aluminum construction.
- Horizontally hinged doors are constructed of .100 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Doors are attached to the hull of box with stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Door is held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop door down to 180°.
- Top panel of the box forms a drip rail over the door.
- A full size, stainless steel paddle latch is recessed into the door.
- Two keys are furnished per box.
- Doors can be closed with the latch in the locked position.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56 SINGLE LID CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

63-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 157 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56A SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 82 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56AB SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 84 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56AW SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 84 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56B SINGLE LID CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 9.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 157 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56LP SINGLE LID LOW PROFILE CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

63-3/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 146 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56LPA SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 74 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56LPAB SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 76 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56LPAW SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" 2-14", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 76 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56LPB SINGLE LID LOW PROFILE CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

63-3/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 7.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 146 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56LPD SINGLE LID LOW PROFILE DEEP CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

63-3/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 8.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2/14", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 153 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C56LPDA SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

Revised 8/6/2014

**BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 8.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 77 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C56LPDAB SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 8.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 79 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C56LPDAW SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 8.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 79 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C56LPDB SINGLE LID LOW PROFILE DEEP CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

64" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 8.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full-size stainless-steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 153 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63 SINGLE LID CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 178 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63A SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

3/30/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 97 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63AB SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 99 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63AW SINGLE LID ALUMINUM CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 99 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63B SINGLE LID CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 178 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63D SINGLE LID DEEP CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full-size stainless-steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 205 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63DA SINGLE LID ALUMINUM DEEP CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-3/4" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 104 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63DAB SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 106 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63DAW SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 106 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63DB SINGLE LID DEEP CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 25-11/16" deep.  
Approximate volume is 19.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 205 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63LP SINGLE LID LOW PROFILE CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 170 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63LPA SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 3/30/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 86 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63LPAB SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63LPAW SINGLE LID ALUMINUM LOW PROFILE CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 3/30/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63LPB SINGLE LID LOW PROFILE CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 14-11/16" deep.  
Approximate volume is 9.1 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 170 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63LPD SINGLE LID LOW PROFILE DEEP CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 180 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63LPDA SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2 overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight 90 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63LPDAB SINGLE LID ALUMINUM**  
**LOW PROFILE DEEP CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight 92 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63LPDB SINGLE LID LOW PROFILE DEEP CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/1/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 180 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63LPNA SINGLE LID ALUMINUM**  
**LOW PROFILE NARROW CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 15-1/2" wide, 14-11/16" deep.  
Approximate volume is 6.8 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 70 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63LPNAB SINGLE LID ALUMINUM**  
**LOW PROFILE NARROW CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 15-1/2" wide, 14-11/16" deep.  
Approximate volume is 6.8 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/2" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 72 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63LPNAW SINGLE LID ALUMINUM**  
**LOW PROFILE NARROW CROSSBOX SPECIFICATIONS**  
**WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 15-1/2" wide, 14-11/16" deep.  
Approximate volume is 6.8 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 14-3/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 72 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63S SINGLE LID SHALLOW CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 174 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63SA SINGLE LID SHALLOW ALUMINUM CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 92 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63SAB SINGLE LID SHALLOW ALUMINUM CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 94 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63SAW SINGLE LID SHALLOW ALUMINUM CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 94 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63SB SINGLE LID SHALLOW CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 14-3/16" deep.  
Approximate volume is 10.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 19-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 174 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63T SINGLE LID CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 7-3/16" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted for dividers on 2" centers.
- Box comes with 3 adjustable dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 130 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63TB SINGLE LID CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 20" wide, 7-3/16" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted for dividers on 2" centers.
- Box comes with 3 adjustable dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 130 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63W SINGLE LID WIDE CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two double-spring type lid prop assemblies assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 231 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63WA SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 124 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63WAB SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 126 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63WAW SINGLE LID ALUMINUM WIDE CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 126 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63WB SINGLE LID WIDE CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 19.4 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Four spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 231 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63WD SINGLE LID WIDE AND DEEP CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two double-spring type lid prop assemblies assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 255 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63WDA SINGLE LID ALUMINUM**  
**WIDE AND DEEP CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

Revised 4/2/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 134 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63WDAB SINGLE LID ALUMINUM**  
**WIDE AND DEEP CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

Revised 4/2/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 136 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63WDAW SINGLE LID ALUMINUM**  
**WIDE AND DEEP CROSSBOX SPECIFICATIONS**  
**WHITE DIAMOND TREADPLATE**

Revised 4/2/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 136 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **C63WDB SINGLE LID WIDE AND DEEP CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

71-1/4" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 27.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Four spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 255 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63WSA SINGLE LID ALUMINUM**  
**WIDE SHALLOW CROSSBOX SPECIFICATIONS**  
**BRIGHT DIAMOND TREADPLATE**

Revised 4/2/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 14-3/16" deep.  
Approximate volume is 16 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 116 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63WSAB SINGLE LID ALUMINUM**  
**WIDE SHALLOW CROSSBOX SPECIFICATIONS**  
**BLACK DIAMOND TREADPLATE**

Revised 4/2/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 14-3/16" deep.  
Approximate volume is 16 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 118 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**C63WSAW SINGLE LID ALUMINUM**  
**WIDE SHALLOW CROSSBOX SPECIFICATIONS**  
**WHITE DIAMOND TREADPLATE**

Revised 4/2/2020

**BOX DIMENSIONS AS FOLLOWS:**

71-1/2" overall length, 30" wide, 14-3/16" deep.  
Approximate volume is 16 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the ends of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Sliding tray, 29-1/4" x 19-1/4" x 2-1/4", with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 118 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**FD301024 FLOOR DRAWER SPECIFICATIONS**  
**WHITE POWDER COAT FINISH**

Revised 3/31/2020

**DIMENSIONS AS FOLLOWS:**

30-1/4" overall length, 11-5/8" overall height and 24-5/8" overall depth.  
6" drawer height

**TO INCLUDE THE FOLLOWING FEATURES:**

- 14GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti-slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 153 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**FD301024B FLOOR DRAWER SPECIFICATIONS**  
**BLACK POWDER COAT FINISH**

Revised 3/31/2020

**DIMENSIONS AS FOLLOWS:**

30-1/4" overall length, 11-5/8" overall height and 24-5/8" overall depth.  
6" drawer height

**TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti-slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Weight: 153 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**FD301048 FLOOR DRAWER SPECIFICATIONS**  
**WHITE POWDER COAT FINISH**

Revised 3/31/2020

**DIMENSIONS AS FOLLOWS:**

30-1/4" overall length, 11-5/8" overall height and 48-5/8" overall depth.  
6" drawer height

**TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti-slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 248 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**FD301048B FLOOR DRAWER SPECIFICATIONS**  
**BLACK POWDER COAT FINISH**

Revised 3/31/2020

**DIMENSIONS AS FOLLOWS:**

30-1/4" overall length, 11-5/8" overall height and 48-5/8" overall depth.  
6" drawer height

**TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti-slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Weight: 248 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**FD401024 FLOOR DRAWER SPECIFICATIONS**  
**WHITE POWDER COAT FINISH**

Revised 3/31/2020

**DIMENSIONS AS FOLLOWS:**

40-1/4" overall length, 11-5/8" overall height and 24-5/8" overall depth.  
6" drawer height

**TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti-slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 186 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**FD401024B FLOOR DRAWER SPECIFICATIONS**  
**BLACK POWDER COAT FINISH**

Revised 7/12/2013

**DIMENSIONS AS FOLLOWS:**

40-1/4" overall length, 11-5/8" overall height and 24-5/8" overall depth.  
6" drawer height

**TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 186 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**FD401048 FLOOR DRAWER SPECIFICATIONS**  
**WHITE POWDER COAT FINISH**

Revised 7/12/2013

**DIMENSIONS AS FOLLOWS:**

40-1/4" overall length, 11-5/8" overall height and 48-5/8" overall depth.  
6" drawer height

**TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 290 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**FD401048B FLOOR DRAWER SPECIFICATIONS**  
**BLACK POWDER COAT FINISH**

Revised 7/12/2013

**DIMENSIONS AS FOLLOWS:**

40-1/4" overall length, 11-5/8" overall height and 48-5/8" overall depth.  
6" drawer height

**TO INCLUDE THE FOLLOWING FEATURES:**

- 14 GA or thicker construction.
- Full size easy to grab paddle latch with 2 keys furnished.
- Drawers are easily removable and glide on heavy duty sealed roller bearings.
- Ribbed D-bulb seal completely around drawer opening.
- Anti slip strips are factory installed on top of unit for added traction.
- Quick and easy installation. Drawer removal not necessary for mounting. Hardware included.
- 1200 lb. top load weight rating (evenly distributed).
- Drawers and 2 full length dividers are slotted on 2" centers.
- Cross dividers are easily added or removed allowing flexible storage.
- Units go through a five-stage zinc phosphate wash, anti-corrosion protection and are finished with a super durable polyester powder coat.
- Weight: 290 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M36-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 8/7/2014

### **BOX DIMENSIONS AS FOLLOWS:**

37-3/16" overall length, 16" wide, 16-1/8" deep.  
Approximate volume is 4.8 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is included.
- Weight: 39 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M36-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

37-3/16" overall length, 16" wide, 16-1/8" deep.  
Approximate volume is 4.8 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 41 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M36-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

37-3/16" overall length, 16" wide, 16-1/8" deep.  
Approximate volume is 4.8 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- A full size, stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Lid is equipped with a gas pressure shock for one-hand opening of the box.
- Lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 41 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M45-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

45-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 131 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M45-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 8/7/2014

### **BOX DIMENSIONS AS FOLLOWS:**

46-3/16" overall length, 20" wide, 19-1/4" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is included.
- Weight: 67 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M45-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

46-3/16" overall length, 20" wide, 19-1/4" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 69 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M45-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

46-3/16" overall length, 20" wide, 19-1/4" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with three 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 69 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M45-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

45-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 10 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 45" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 131 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M54-1 SINGLE LID BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 12-5/8" x 4-1/4" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 129 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M54-1B SINGLE LID BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 12-5/8" x 4-1/4" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 129 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M54-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

54-1/4" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 123 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M54-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

54-1/4" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 123 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M54-2 DOUBLE LID BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 12-5/8" x 4-1/4" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 132 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M54-2B DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 12-5/8" x 4-1/4" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids. Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box. Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 132 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M54-2NM DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

54-1/4" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 126 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M54-2NMB DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

54-1/4" overall length, 16" wide, 16-11/16" deep.  
Approximate volume is 8.25 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 54" x 4", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 126 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M54U-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**WHITE POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

54-3/4" overall length, 20" wide, 19" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid is to allow flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 133 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M54U-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BRIGHT DIAMOND TREADPLATE**

Revised 8/15/2014

**BOX DIMENSIONS AS FOLLOWS:**

55-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is included.
- Weight: 67 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M54U-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BLACK POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

55-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 69 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M54U-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**WHITE POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

55-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 69 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M54U-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BLACK POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

54-3/4" overall length, 20" wide, 19-1/16" deep.  
Approximate volume is 11.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid is to allow flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 133 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M58FP-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

58-3/4" overall length, 18" wide, 11-1/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Anti-slip strips are factory installed on top of unit for added traction.
- Mounting hardware and mounting instructions included.
- Weight: 115 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M58FP-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS BRIGHT DIAMOND TREADPLATE**

| 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

| 59-3/16" overall length, 18" wide, 11-1/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware and mounting instructions included.
- Weight: 86 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M58FP-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

59-3/16" overall length, 18" wide, 11-1/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M58FP-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

59-3/16" overall length, 18" wide, 11-1/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M58FP-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

58-3/4" overall length, 18" wide, 11-1/8" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Anti-slip strips are factory installed on top of unit for added traction.
- Attaching hardware is included.
- Weight: 115 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M58U-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**WHITE POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

58-3/4" overall length, 20" wide, 19-1/16" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid is to allow flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 144 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M58U-1NMA SINGLE LID, CHEST TYPE, ALUMINUM BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BRIGHT DIAMOND TREADPLATE**

Revised 8/15/2014

**BOX DIMENSIONS AS FOLLOWS:**

59-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware and mounting instructions included.
- Weight: 71 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M58U-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

59-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on- short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 73 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M58U-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**WHITE DIAMOND TREADPLATE**

Revised 4/01/2020

**BOX DIMENSIONS AS FOLLOWS:**

59-3/16" overall length, 20" wide, 19-1/8" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on- short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 73 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M58U-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**LOWER BOX FRONT DIAGONALLY TAPERED**  
**BLACK POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

58-3/4" overall length, 20" wide, 19-1/16" deep.  
Approximate volume is 12.25 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid is to allow flush mounting to the front of the pickup box.
- Lower front face of the box is diagonally tapered to accommodate wheel wells on short bed trucks.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 144 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60-1 SINGLE LID BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/2" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 15-1/2" x 4-1/2" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 178 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60-1B SINGLE LID BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/2" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 15-1/2" x 4-1/2" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full-size stainless-steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 178 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 168 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 168 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60-2 DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/2" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 15-1/2" x 4-1/2" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box, and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of each lid.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 180 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60-2B DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/2" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- 10 gauge mounting brackets 15-1/2" x 4-1/2" welded to each end of the box.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box, and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 180 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60-2NM DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- A spring type lid prop assists in the opening and closing of each lid.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 171 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60-2NMB DOUBLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 20" wide, 19-3/16" deep.  
Approximate volume is 13.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Spring type lid props assist in the opening and closing of the lids.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Fixed tray, 60" x 6", welded into the back wall of the box.
- Tray comes with 3 fixed dividers.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 171 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60FW-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 19-3/16" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 164 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60FW-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 8/15/2014

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware and mounting instructions included.
- Weight: 86 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60FW-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60FW-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **M60FW-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 19-3/16" deep.  
Approximate volume is 15.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 164 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M60SB-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**WHITE POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 19-3/16" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware and mounting instructions included.
- Weight: 172 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M60SB-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**BRIGHT DIAMOND TREADPLATE**

Revised 8/15/2014

**BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware and mounting instructions included.
- Weight: 82 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M60SB-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with ¼" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 84 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M60SB-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**WHITE DIAMOND TREADPLATE**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 19-1/4" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with ¼" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 84 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**M60SB-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS**  
**END OFFSETS FOR INSTALLATION OVER WHEEL WELL**  
**BLACK POWDER FINISH**

Revised 8/15/2014

**BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 19-3/16" deep.  
Approximate volume is 13 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid to allow flush mounting to the front of the pickup box.
- 6" x 9-1/2" recess in the lower ends of the box to clear the wheel wells in short bed trucks.
- Small part tray 23" long, 6" wide, and 4" deep in each end of the box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 172 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **MTB60-1NM SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 24-3/16" deep.  
Approximate volume is 19.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 182 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **MTB60-1NMA SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 8/15/2014

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 24-1/4" deep.  
Approximate volume is 19.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Attaching hardware is included.
- Weight: 91 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **MTB60-1NMAB SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 24-1/4" deep.  
Approximate volume is 13 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 93 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **MTB60-1NMAW SINGLE LID ALUMINUM, CHEST TYPE, BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

61-3/16" overall length, 23" wide, 24-1/4" deep.  
Approximate volume is 19.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum and fully welded on all 4 sides.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Two full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Lid is equipped with 2 gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with four 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Attaching hardware is included.
- Weight: 93 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **MTB60-1NMB SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

60-3/4" overall length, 23" wide, 24-3/16" deep.  
Approximate volume is 19.3 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size, stainless steel paddle latches are recessed into the hull of the box and synchronized to allow opening or locking from either side of the vehicle.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Offset in the rear of the lid allows flush mounting to the front of the pickup box.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 182 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **RG10 REAR GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

68" overall length, 9-1/4" wide including brackets, and 27-3/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **RG10B REAR GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

68" overall length, 9-1/4" wide including brackets, and 27-3/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **RG11 REAR GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

68" overall length, 9-1/4" wide including brackets, and 29-1/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **RG11B REAR GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

68" overall length, 9-1/4" wide including brackets, and 29-1/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **RG15 REAR GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

71" overall length, 9-1/4" wide including brackets, and 26-1/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **RG15B REAR GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **REAR GRILL DIMENSIONS AS FOLLOWS:**

71" overall length, 9-1/4" wide including brackets, and 26-1/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper crossbar is 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware and instructions are included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST56U DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- A spring type lid prop assists in the opening and closing of each lid.
- 2 keys are furnished per box.
- Sliding tray 19-1/4" x 14-3/4" x 2-1/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep tray centered while not being used.
- Ribbed D-Bulb seal is installed in each lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 152 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST56UB DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

62-1/2" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 11 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- Spring type lid props assist in the opening and closing of each lid.
- 2 keys are furnished per box.
- Sliding tray 19-1/4" x 14-3/4" x 2-1/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep tray centered while not being used.
- Ribbed D-Bulb seal is installed in each lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 152 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST63 DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- A spring type lid prop assists in the opening and closing of each lid.
- Sliding tray 19-1/4" x 19-1/4" x 2-1/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in each lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 175 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST63A DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/8" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 13 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Lids are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- Two keys are furnished per box.
- Each lid is equipped with a gas shock for one-hand opening of the box.
- Sliding tray 19-1/4" x 19-1/4" x 2-1/4" with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST63AB DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/8" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 13 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Lids are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- Two keys are furnished per box.
- Each lid is equipped with a gas pressure shock for one-hand opening of the box.
- Sliding tray 19-1/4" x 19-1/4" x 2-1/4" with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Black boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST63AW DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70-1/8" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 13 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of .080 bright diamond treadplate aluminum.
- Bottom of the box is constructed of .125 smooth aluminum, and welded in with full arc welds, no spot welds.
- Lids are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" aluminum butt hinges with 1/4" hinge pins.
- Hinges are welded to the box and lid.
- A full size, stainless steel paddle latch is recessed into each lid.
- Two keys are furnished per box.
- Each lid is equipped with a gas pressure shock for one-hand opening of the box.
- Sliding tray 19-1/4" x 19-1/4" x 2-1/4" with a white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- White boxes go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST63B DOUBLE LID "SLANT TOP" CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 20" wide, 17-7/16" deep.  
Approximate volume is 12.5 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- Spring type lid props assist in the opening and closing of each lid.
- Sliding tray 19-1/4" x 19-1/4" x 4-1/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while it is not being used.
- Ribbed D-Bulb seal is installed in each lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 175 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST63W DOUBLE LID WIDE “SLANT TOP” CROSSBOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 18.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- A double-spring type lid prop assembly assists in the opening and closing of each lid.
- Sliding tray 29-1/4" x 19-1/4" x 2-1/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 219 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **ST63WB DOUBLE LID WIDE “SLANT TOP” CROSSBOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 30" wide, 17-7/16" deep.  
Approximate volume is 18.75 cubic feet.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- Spring type lid props assist in the opening and closing of each lid.
- Sliding tray 29-1/4" x 19-1/4" x 2-1/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- .
- Weight: 219 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**ST63WD DOUBLE LID WIDE AND DEEP**  
**“SLANT TOP” CROSSBOX SPECIFICATIONS**  
**WHITE POWDER FINISH**

Revised 4/2/2020

**BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 26.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- A double-spring type lid prop assembly assists in the opening and closing of each lid.
- Sliding tray 29-1/4" x 19-1/4" x 2-1/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- Weight: 248 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**ST63WDB DOUBLE LID WIDE AND DEEP**  
**“SLANT TOP” CROSSBOX SPECIFICATIONS**  
**BLACK POWDER FINISH**

Revised 4/2/2020

**BOX DIMENSIONS AS FOLLOWS:**

70" overall length, 30" wide, 25-11/16" deep.  
Approximate volume is 26.5 cubic feet.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and welded in with full arc welds.
- Lids are constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Each lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- A full size stainless steel paddle latch is recessed into each lid.
- 2 keys are furnished per box.
- Spring type lid props assist in the opening and closing of each lid.
- Sliding tray 29-1/4" x 19-1/4" x 2-1/4" with white super durable polyester powder coat finish.
- Tray comes with 4 adjustable dividers.
- Box is equipped with tray stops to keep the tray centered while not being used.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware is an extruded aluminum mounting clamp that eliminates drilling through the pickup bed rail. Plastic isolator keeps mounting clamp from scratching paint, preventing galvanic corrosion.
- .
- Weight: 248 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TC10814 SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

108-3/4" overall length, 14-1/2" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Weight: 165 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TC10814B SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

108-3/4" overall length, 14-1/2" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Weight: 165 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TC10820 SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

108-3/4" overall length, 20" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Three spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening
- Weight: 195 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TC10820B SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

108-3/4" overall length, 20" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Three spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Weight: 195 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TC9614 SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96-3/4" overall length, 14-1/2" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Weight: 149 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TC9614B SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96-3/4" overall length, 14-1/2" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Weight: 149 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TC9620 SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96-3/4" overall length, 20" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Three spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Weight: 176 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TC9620B SINGLE LID TOP OPENING SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96-3/4" overall length, 20" wide, and 7-1/4" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Box is slotted on 2" centers for dividers.
- Box comes with 8 adjustable dividers.
- A full size stainless steel paddle latch is recessed into the hull of the box.
- Two keys are furnished per box.
- Three spring type lid props assist in the opening and closing of the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening
- Weight: 176 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **RKI TRAY FLDOUT SPECIFICATIONS** **WHITE POWDER FINISH**

3/31/2020

### **TRAY DIMENSIONS AS FOLLOWS:**

28-1/8" overall length, 10-3/8" wide, 2-1/4" deep TRAY SIZE.

29-3/8" overall length, 11-3/8" wide, 9-7/8" deep OVERALL CABINET SIZE.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Two tray fold-out assembly.
- Trays are constructed of 18 gauge cold rolled steel.
- Fold-out assembly comes with 12 dividers.
- Trays go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 29 lbs.

**TRAY FLDOUT is OPTIONAL for US and UST boxes. TRAY FLDOUT can also be used in some Service Body applications.**

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.

RKI, Inc.

2301 Central Parkway Houston, TX 77092

713.688.4414

Fax: 713.688.8982

[www.rkius.com](http://www.rkius.com)



**RKI TRAY M SPECIFICATIONS**  
**WHITE POWDER FINISH**

3/31/2020

**TRAY DIMENSIONS AS FOLLOWS:**

22-1/2" overall length, 19-1/4" wide, 2-1/4" deep.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 18 gauge cold rolled steel.
- Tray comes with 4 dividers.
- Trays go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 10 lbs.

**TRAY M is OPTIONAL for THE FOLLOWING BOXES:**

M54U-1NM, M58U-1NM, M60FW-1NM, M60SB-1NM, MTB60-1NM  
M54U-1NMA, M58U-1NMA, M60FW-1NMA, M60SB-1NMA, MTB60-1NMA

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**RKI TRAY SLPW SPECIFICATIONS**  
**WHITE POWDER FINISH**

3/31/2020

**TRAY DIMENSIONS AS FOLLOWS:**

12-3/8" overall length, 11-5/8" wide, 2-1/4" deep.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 18 gauge cold rolled steel.
- Tray comes with 2 dividers.
- Trays go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 4 lbs.

**TRAY SLPW is OPTIONAL for SLPW boxes.**

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**RKI TRAY ST SPECIFICATIONS - NEW STYLE**  
**EFFECTIVE QA# 3639**  
**WHITE POWDER FINISH**

3/31/2020

**TRAY DIMENSIONS AS FOLLOWS:**

19-1/4" overall length, 19-1/4" wide, 2-1/4" deep.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 22 gauge cold rolled steel.
- Tray comes with 4 adjustable dividers.
- Trays go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 13 lbs.

**TRAY ST STANDARD IN THE FOLLOWING BOXES:**

ST63, ST63A  
C63, C63D, C63LP, C63LPD, C63S  
C63A, C63DA, C63LPA, C63LPDA, C63SA

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**RKI TRAY STS SPECIFICATIONS**  
**WHITE POWDER FINISH**

3/31/2020

**TRAY DIMENSIONS AS FOLLOWS:**

19-1/2" overall length, 8-7/8" wide, 2-1/4" deep.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 22 gauge cold rolled steel.
- Tray comes with 4 adjustable dividers.
- Trays go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 6 lbs.

**TRAY ST STANDARD IN THE FOLLOWING BOXES:**

50STS, 61STS, 67STS

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**RKI TRAY STW SPECIFICATIONS**  
**WHITE POWDER FINISH**

3/31/2020

**TRAY DIMENSIONS AS FOLLOWS:**

29-1/4" overall length, 19-1/4" wide, 2-1/4" deep.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 18 gauge cold rolled steel.
- Tray comes with 4 adjustable dividers.
- Trays go through a five-stage zinc phosphate wash, anti-corrosion protection, and are finished with a white super durable polyester powder coat.
- Weight: 13 lbs.

**TRAY STW STANDARD IN THE FOLLOWING BOXES:**

ST63W, ST63WD  
C63W, C63WD  
C63WA, C63WDA, C63WSA

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**RKI TRAY SW SPECIFICATIONS**  
**WHITE POWDER FINISH**

Revised 4/1/2020

**TRAY DIMENSIONS AS FOLLOWS:**

19-1/2" overall length, 14-3/8" wide, 2-1/4" deep.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of 18 gauge cold rolled steel.
- Tray comes with 4 dividers.
- Trays go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 8 lbs.

**TRAY SW INCLUDED WITH THE FOLLOWING BOXES:**

ST56U  
C56, C56LP, C56LPD  
C56A, C56LPA, C56LPDA, C63LPNA

**TRAY SW is OPTIONAL for ALL S-Series truck boxes except low profile models.**

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **RKI TRAY US SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **TRAY DIMENSIONS AS FOLLOWS:**

41-1/2" overall length, 8-7/8" wide, 2-1/4" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Tray is constructed of **18** gauge cold rolled steel.
- Tray comes with 8 dividers.
- Trays go through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Weight: 12 lbs.

**TRAY US is OPTIONAL for US and UST boxes.**

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TTB34 SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

35-1/4" overall length, 15" wide, 22" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware included.
- Weight: 72 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **TTB34B SINGLE LID CHEST TYPE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

35-1/4" overall length, 15" wide, 22" deep.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of the box is constructed of 14 gauge cold rolled steel.
- Bottom of the box is constructed of 14 gauge cold rolled steel, and fully welded on all 4 sides.
- Lid is constructed of 14 gauge cold rolled steel with a 14 gauge cold rolled steel inner stiffener.
- Welds are full arc welds, no spot welds.
- Full size stainless steel paddle latches are recessed into the hull of the box.
- Two keys are furnished per box.
- Two spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with two 4" stainless steel butt hinges.
- Hinges are welded to the box and lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the box opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Attaching hardware is included.
- Weight: 72 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US48A SINGLE DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Door is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chains detach to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US48AB SINGLE DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Door is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chains detach to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting Hardware Included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US48AW SINGLE DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 4/2/2020

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Door is constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chains detach to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 47 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US48C SINGLE DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Welds are full arc welds, no spot welds.
- Door is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 98 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US48CB SINGLE DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

48" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Welds are full arc welds, no spot welds.
- Door is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the door.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into the door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 98 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US72A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 3/31/2010

### **BOX DIMENSIONS AS FOLLOWS:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 68 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US72AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 68 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US72AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 68 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US72C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOW:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door facing.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 138 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US72CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOW:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door facing.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 138 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US78C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOW:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door facing.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 150 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US78CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOW:**

72" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door facing.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 150 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US90A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full-size stainless-steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 82 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US90AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 82 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US90AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chains detach to swing the doors down to 180°.
- A full-size stainless-steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 82 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US90C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 168 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US90CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

90" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 168 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US96A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BRIGHT DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors are held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop doors down to 180°.
- A full size, stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 87 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US96AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **BLACK DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors are held in the open horizontal position with heavy duty machine chain.
- Chains are easily detachable to drop the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 87 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US96AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS** **WHITE DIAMOND TREADPLATE**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Box is constructed of .080 bright diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Doors are constructed of .080 bright diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Each door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and full length 5/16" stainless steel hinge pins.
- Hinges are riveted to the box.
- Top panel of the box forms a drip rail over the door.
- Doors are held in the open horizontal position with heavy duty machine chain.
- Chains are easily detachable to drop the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a recessed channel that runs the full perimeter of the door opening.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Door has a formed knife edge on all 4 sides that contacts the seal when the door is closed.
- Mounting hardware included.
- Weight: 87 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US96C TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors are held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 176 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **US96CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 3/31/2020

### **BOX DIMENSIONS AS FOLLOWS:**

96" overall length, 16-1/2" overall height, and 12-1/2" overall depth.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- 14 gauge cold rolled steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Welds are full arc welds, no spot welds.
- Doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Top panel of the box forms a drip rail over the doors.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 176 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST48C SINGLE DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**WHITE POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

48-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with three 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged door is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware included.
- Weight: 151 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST48CB SINGLE DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK POWDER FINISH**

Revised 3/31/2020

**BOX DIMENSIONS AS FOLLOWS:**

48-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with three 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged door is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Door is attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Door has heavy duty machine chain to hold it in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Door can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door opening.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware included.
- Weight: 151 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST60C TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**WHITE POWDER FINISH**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

60-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware included.
- Weight: 188 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST60CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK POWDER FINISH**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

60-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware included.
- Weight: 188 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST72A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 107 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST72AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS  
WITH INTEGRAL TOP OPENING COMPARTMENT  
BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 107 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST72AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 107 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST72C TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**WHITE POWDER FINISH**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware included.
- Weight: 226 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST72CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK POWDER FINISH**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

73" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware included.
- Weight: 226 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST90C TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**WHITE POWDER FINISH**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

90-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware included.
- Weight: 261 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST90CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK POWDER FINISH**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

90-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware included.
- Weight: 261 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST96A TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BRIGHT DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

97" overall length, 20" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with two gas shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Door hinges are riveted to the box.
- Doors are held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop doors down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Mounting hardware included.
- Weight: 142 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST96AB TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

97" overall length, 20" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware included.
- Weight: 142 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST96AW TWO DOOR ALUMINUM UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**WHITE DIAMOND TREADPLATE**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

97" overall length, 20" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of .080 diamond treadplate aluminum.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of .080 diamond treadplate aluminum with an inner stiffener of .090 smooth aluminum.
- Lid is equipped with gas pressure shocks for one-hand opening of the box.
- Lid is attached to the hull of the box with five 4" aluminum butt hinges with 1/4" hinge pins that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of .080 diamond treadplate aluminum, with a .090 smooth aluminum inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware included.
- Weight: 142 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST96C TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**WHITE POWDER FINISH**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

96-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Four spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with four 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Door hinges are welded to the box.
- Doors are held in the open position with heavy-duty machine chains.
- Chains are easily detachable to drop doors down to 180°.
- A full size, stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- Mounting hardware included.
- Weight: 287 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**UST96CB TWO DOOR UPPER SIDE BOX SPECIFICATIONS**  
**WITH INTEGRAL TOP OPENING COMPARTMENT**  
**BLACK POWDER FINISH**

Revised 4/1/2020

**BOX DIMENSIONS AS FOLLOWS:**

96-1/2" overall length, 20-1/8" overall height, and 14-1/2" overall depth.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Hull of box is constructed of 14 gauge cold rolled steel.
- Welds are full arc welds, no spot welds.
- Box incorporates a 4-1/2" deep top opening compartment.
- Top opening compartment has adjustable divider slots on 2" centers.
- Lid is constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Spring type lid props assist in the opening and closing of the lid.
- Lid is attached to the hull of the box with six 4" stainless steel butt hinges that are welded to the hull of the box and the lid.
- Ribbed D-Bulb seal is installed in the lid to seal against the flange around the top compartment opening.
- Lid design forms a drip rail over the doors.
- 8 dividers are furnished for top opening compartment.
- Front horizontally hinged doors are constructed of 14 gauge cold rolled steel, with a 14 gauge cold rolled steel inner stiffener.
- Doors are attached to the hull of the box with 3 stainless steel pillow block type hinges with self-lubricating bushings and 5/16" stainless steel hinge pins.
- Hinges are welded to the box.
- Doors have heavy duty machine chain to hold them in the horizontal position.
- Chain detaches to swing the door down to 180°.
- A full size stainless steel paddle latch is recessed into each door.
- Doors can be closed with the latch in the locked position.
- Two keys are furnished per box.
- Ribbed D-Bulb seal is installed in a full perimeter channel around the door openings.
- A knife edge is formed into the door to contact the seal in the door channel.
- Box goes through a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- Mounting hardware included.
- Weight: 287 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG10 NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 28" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 64 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG15AW WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

9/29/2020

### **DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 26-1/2" overall height, to bottom of crossbar height 21-3/4".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Louvers are constructed of 1/8" formed aluminum with four 1/2" round bar aluminum vertical support rods, support rods are welded to each louver and top and bottom crossbars.
- Louvers are assembled to provide an unobstructed view of the trucks center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a white super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 48 lbs.
- Approximate Shipping Weight 55 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG15AW NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS**  
**WHITE POWDER FINISH**

9/29/2020

**DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 26-1/2" overall height, to bottom of crossbar height 21-3/4".

**TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a white super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 33 lbs.
- Approximate Shipping Weight 40 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG15AB WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

9/29/2020

### **DIMENSIONS AS FOLLOWS:**

71-1/18" overall length, 26-1/2" wide including mounting brackets, and 26-1/2" overall height, to bottom of crossbar height 21-1/4".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Louvers are constructed of 1/8" formed aluminum with four 1/2" round bar aluminum vertical support rods, support rods are welded to each louver and top and bottom crossbars.
- Louvers are assembled to provide an unobstructed view of the trucks center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a black super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 48 lbs.
- Approximate Shipping Weight 55 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG15AB NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS**  
**BLACK POWDER FINISH**

9/29/2020

**DIMENSIONS AS FOLLOWS:**

71-1/18" overall length, 26-1/2" wide including mounting brackets, and 26-1/2" overall height, to bottom of crossbar height 21-3/4".

**TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a black super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 33 lbs.
- Approximate Shipping Weight 40 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG11AW WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

9/29/2020

### **DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 29-7/16" overall height, to bottom of crossbar height 24-13/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Louvers are constructed of 1/8" formed aluminum with four 1/2" round bar aluminum vertical support rods, support rods are welded to each louver and top and bottom crossbars.
- Louvers are assembled to provide an unobstructed view of the trucks center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a white super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 49 lbs.
- Approximate Shipping Weight 55 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG11AW NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS**  
**WHITE POWDER FINISH**

9/29/2020

**DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 29-7/16" overall height, to bottom of crossbar height 24-13/16".

**TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 35 lbs.
- Approximate Shipping Weight 42 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG11AB WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

9/29/2020

### **DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 29-7/16" overall height, to bottom of crossbar height 24-13/16".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Louvers are constructed of 1/8" formed aluminum with four 1/2" round bar aluminum vertical support rods, support rods are welded to each louver and top and bottom crossbars.
- Louvers are assembled to provide an unobstructed view of the trucks center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a black super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 49 lbs.
- Approximate Shipping Weight 55 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG11AB NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS**  
**BLACK POWDER FINISH**

9/29/2020

**DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 29-7/16" overall height, to bottom of crossbar height 24-13/16".

**TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a black super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 35 lbs.
- Approximate Shipping Weight 42 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG10AW WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

9/29/2020

### **DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 28" overall height, to bottom of crossbar height 23-3/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Louvers are constructed of 1/8" formed aluminum with four 1/2" round bar aluminum vertical support rods, support rods are welded to each louver and top and bottom crossbars.
- Louvers are assembled to provide an unobstructed view of the trucks center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a white super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 49 lbs.
- Approximate Shipping Weight 56 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG10AW NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

9/29/2020

### **DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 28" overall height, to bottom of crossbar height 23-3/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a white super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 35 lbs.
- Approximate Shipping Weight 42 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG10AB WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

9/29/2020

### **DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 28" overall height, to bottom of crossbar height 23-3/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Louvers are constructed of 1/8" formed aluminum with four 1/2" round bar aluminum vertical support rods, support rods are welded to each louver and top and bottom crossbars.
- Louvers are assembled to provide an unobstructed view of the trucks center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a black super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 49 lbs.
- Approximate Shipping Weight 56 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG10AB "NO LOUVER" WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

9/29/2020

### **DIMENSIONS AS FOLLOWS:**

71-1/8" overall length, 26-1/2" wide including mounting brackets, and 28" overall height, to bottom of crossbar height 23-3/8".

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Window Grille and Mounting Legs are constructed of heavy-duty commercial grade aluminum.
- End plates are 1/2" x 3" aluminum flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with 1/4" wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are 1/4" aluminum flatbar.
- Window Grille goes through a five stage state-of-the art metal pretreatment system and are finished with a black super durable polyester powder coat.
- Mounting hardware eliminates drilling through the pickup bed rail and is compatible with steel or aluminum truck beds.
- Mounting instructions included.
- Approximate Product Weight 35 lbs.
- Approximate Shipping Weight 42 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG10 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 28" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG10B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 28" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 64 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG10B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 28" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG11 NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 28-3/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 65 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG11 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 28-3/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG11B NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 28-3/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 65 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG11B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 28-3/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 88 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG14 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-7/8" overall length, 26" wide including brackets, and 27" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 78 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG14B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-7/8" overall length, 26" wide including brackets, and 27" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 57 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG14B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-7/8" overall length, 26" wide including brackets, and 27" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 78 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG14 NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS**  
**WHITE POWDER FINISH**

Revised 4/2/2020

**NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

59-7/8" overall length, 26" wide including brackets, and 27" tall.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 57 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG15 NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 25-1/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 62 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG15 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

Revised 4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 25-1/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG15B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS**  
**BLACK POWDER FINISH**

Revised 4/2/2020

**NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 25-1/4" tall.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 62 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG15B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

Revised 4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

71-5/8" overall length including brackets, 26" wide including brackets, and 25-1/4" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG16 NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS**  
**WHITE POWDER FINISH**

4/2/2020

**NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

62-7/8" overall length including brackets, 26" wide including brackets, and 22-3/8" tall.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 62 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG16 WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

62-1/2" overall length including brackets, 26" wide including brackets, and 22-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG16B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS**  
**BLACK POWDER FINISH**

4/2/2020

**NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

62-7/8" overall length including brackets, 26" wide including brackets, and 22-3/8" tall.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 62 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG16B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

62-7/8" overall length including brackets, 26" wide including brackets, and 22-3/8" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG17 NL "NO LOUVER" WINDOW GRILLE SPECIFICATIONS** **WHITE POWDER FINISH**

4/2/2020

### **NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

62-7/8" overall length including brackets, 26" wide including brackets, and 25-1/2" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 62 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG17 WINDOW GRILLE SPECIFICATIONS**  
**WHITE POWDER FINISH**

4/2/2020

**WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

62-7/8" overall length including brackets, 26" wide including brackets, and 25-1/2" tall.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable white polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



**WG17B NL “NO LOUVER” WINDOW GRILLE SPECIFICATIONS**  
**BLACK POWDER FINISH**

4/2/2020

**NO LOUVER WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

762-7/8" overall length including brackets, 26" wide including brackets, and 25-1/2" tall.

**TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 62 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.



## **WG17B WINDOW GRILLE SPECIFICATIONS** **BLACK POWDER FINISH**

4/2/2020

### **WINDOW GRILLE DIMENSIONS AS FOLLOWS:**

62-7/8" overall length including brackets, 26" wide including brackets, and 25-1/2" tall.

### **TO INCLUDE THE FOLLOWING FEATURES:**

- Steel construction with a five-stage state-of-the art metal pretreatment anti-corrosion protection system and is finished with a super durable black polyester powder coat.
- End plates are 1/2" x 3" cold rolled steel flatbar.
- Upper and lower crossbars are 2" x 2" square tubing with .065 wall.
- Louvers are constructed of 14 gauge cold rolled steel with four 1/2" round rod vertical supports.
- Louvers are assembled as to allow an unobstructed view of the center high mount stop light.
- Welds are full arc welds, no spot welds.
- Mounting brackets are of 3/16" steel construction.
- Mounting hardware included.
- Weight: 83 lbs.

In order to provide the most innovative and progressive equipment, all specifications and designs are subject to change without notice.